

How to Install & Run CMS IntelliCAD PE Plus Network - Steps Sequence

1) Download CMS NKLS and CMS IntelliCAD PE+ Network installers. Backup such files.

2) Install CMS NKLS at a LAN Windows Server or a LAN Machine serving as "CMS license server"

3) Install CMS IntelliCAD PE+ Network on all LAN Client Windows 64-bit machines that may run CMS IntelliCAD software.

4) Run "CMS NKLS" and "CMS NKLS Browser". Make sure to allow CMS NKLS running through the system firewall. Such machine needs to keep it's IP address all the time. If, for some reason, it changes the IP address, you'll have to re-run "CMS NKLS Browser" to broadcast its IP address until all clients update the IP address of CMS NKLS. That will only happen after running CMS IntelliCAD at each client system.

5) Run CMS IntelliCAD at client systems and follow instructions. Make sure to allow "CMS IP Address Receiver" through the system firewall. Update IP address of CMS Server upon notice. Close "CMS NKLS Browser" after all CMS IntelliCAD clients systems update the CMS NKLS IP address location.

6) Run "CMS Icad Register" desktop shortcut and hit the "Register later" button" if running CMS IntelliCAD in DEMO mode, or ACTIVATE a Network license (activating the license from one of the LAN clients is enough). Refer to registration instructions available at the download section of https://intellicadms.com

7) Finally, CMS IntelliCAD will run through CMS IntelliCAD desktop shortcut.



Notice!

CMS IntelliCAD PE+ Network allows seats **borrowing or roaming** intended for offline use; Review instructions at the next page.

> ©1993-2021. CAD-MANUFACTURING SOLUTIONS, INC. IntelliCAD and the IntelliCAD logo are registered trademarks of the IntelliCAD Technology Consortium in the United States and other countries. All other trademarks are property of th respective owners.

CAD-MANUFACTURING SOLUTIONS, INC. PO Box 1261 Azle - Texas TX 76098 - USA Phone: +1 (501) 588-7970 (Sales support ONLY) Web: https://intellicadms.com Email: register@etoolbox.com



How to Borrow or Roaming a Network seat – Steps Sequence

CMS IntelliCAD PE Plus Network license allows users to borrow or roam a seat from the licensed LAN network. Typically this is required when an user needs to work offline.

1) IMPORTANT: The system running CMS NKLS server software must not change the IP address with time; 2) Go to Microsoft Windows® desktop Start and browse for the CMS programs folder > click Roam application; optionally, search for "ROAM" at Windows® search and click ENTER;



3) Enter the number of days planned for offline use, and click "Check out";

😽 Roam Utility			×
The Roam utility allows you to check out a	icense from the licen	se server.	
To check out a license, enter the roaming p To return the license, click the 'Return' but		then dick the 'Cheo	k Out ^r button.
Roaming period: 🛐 🚖 day(s)			
	Return	Check Out	Close

4) When returning the seat to the licensed LAN, connect the client system to the LAN network, run step 2 again. Then click "Return";



©1993-2021. CAD-MANUFACTURING SOLUTIONS, INC. IntelliCAD and the IntelliCAD logo are registered trademarks of the IntelliCAD Technology Consortium in the United States and other countries. All other trademarks are property of th respective owners.



How to add specifc client IP addresses to CMS NKLS License Manager Steps Sequence

Run CMS NKLS license manager at the LAN server; Go to the menu & click **Server** > **Properties**; Add the starting IP address: 10.255.1.X and ending IP address: 10.255.1.Y as examples; DISABLED "Allow NAT Connections checkbox"; Now click the **Add** button;

The list to right must appear as 10.255.1.1 - 10.255.1.255 with no "[...]"

Port: 1245 Idle Time: 3	Port: 1245 Idle Time: 3 minute(s) ✓ Default port ✓ Default idle time ✓ Specify User Addresses Starting IP Address: 010.255.001.001 - 010.255.001.255 Image: Im	Main	
Specify User Addresses Specify User Addresses Starting IP Address: Secify User Address: Add > Specify User Physical Addresses MAC Addr: Add > < Remove letKey Manager Authentication	Default port Default idle time Specify User Addresses Starting IP Address: Image:	Caption:	
☑ Default port ☑ Default idle time ☑ Specify User Addresses ☑ 010:255:001.001 - 010:255:001:255 ☑ Specify IP Address: ☑ ☑ Add > < Remoye ☑ Specify User Physical Addresses ☑ ☑ Add > < Remoye	Obefault port Specify User Addresses Starting IP Address: Allow NAT Connections IP Addr: Add > < Remove Specify User Physical Addresses MAC Addg: < Add > < Remove NetKey Manager Authentication Usgr: Password:	Port: 1245	Idle Time: 3 📥 minute(s)
Specify User Addresses itarting IP Address: itarting IP Addresses Add > Add > Specify User Physical Addresses MAC Addg: Add > Kemove	Specify User Addresses Starting IP Address: Ending IP Address: Allow NAT Connections IP Addr: Add > Specify User Physical Addresses MAC Addg: Add > Remove NetKey Manager Authentication Usgr: Password:		
btarting IP Address: inding IP Addresses Add > inding IP Addresses MAC Addresses MAC Addresses Add > inding IP Addresses	Starting IP Address: Ending IP Address: Ending IP Address: Allow NAT Connections IP Addr: Add > Specify User Physical Addresses MAC Addg: Add > NetKey Manager Authentication Usgr: Password:	Sciulit port	
inding IP Address: inding	Jathing in Address: Ending IP Address: Ending IP Address: Allow NAT Connections IP Addr: Add > Kemove Specify User Physical Addresses MAC Addg: Add > Kemove NetKey Manager Authentication Usgr: Password:	Specify User Addresses 🚽	
Ending IP Address: Allow NAT Connections — IP Addr: Add > < Remove Specify User Physical Addresses MAC Addr: Add > < Remove letKey Manager Authentication Jsgr:	Ending IP Address: Allow NAT Connections IP Addr: Add > < Remove	Starting IP Address:	010.255.001.001 - 010.255.001.255
Allow NAT Connections IP Addr: . Add > < Remove	Allow NAT Connections IP Addr: Add > Add > Specify User Physical Addresses MAC Addg: Add > Remove NetKey Manager Authentication Usgr: Password:		
Allow NAT Connections IP Addr:	Allow NAT Connections IP Addr: Add > Add > Specify User Physical Addresses MAC Addg: Add > Kemove NetKey Manager Authentication User: Password:		
IP Addr: Add > < Remove Specify User Physical Addresses MAC Addg: Add > < Remove letKey Manager Authentication Jsgr:	IP Addr: Add > Add > Remove MAC Addg: - MAC Addg: - MAC Addg: - MAC Addg: - MAC Addg: - Add > NetKey Manager Authentication Usgr: Password:		
Add > < Remove	Add > < Remove		
Specify User Physical Addresses MAC Addg: Add > ketKey Manager Authentication User:	Specify User Physical Addresses MAC Addg: Add > Add > Kemove NetKey Manager Authentication User: Password:		
MAC Addr	MAC Addg: Add > < Remove NetKey Manager Authentication Usg:: Password:	<u>A</u> dd > < Remo <u>v</u> e	2
MAC Addr	MAC Addg: Add > < Remove NetKey Manager Authentication Usg:: Password:		
Add > < Remove	Add > < Remove	Specify User Physical Addr	esses
letKey Manager Authentication	NetKey Manager Authentication Us <u>e</u> r: Pass <u>w</u> ord:	MAC Add <u>r</u> :	
letKey Manager Authentication	NetKey Manager Authentication Us <u>e</u> r: Pass <u>w</u> ord:		
Js <u>e</u> r:	Us <u>e</u> r: Pass <u>w</u> ord:	A <u>d</u> d > < Re <u>m</u> ove	
Js <u>e</u> r:	Us <u>e</u> r: Pass <u>w</u> ord:		
	Password:		on
Dass <u>w</u> ord:		Us <u>e</u> r:	
	<u>O</u> K Appl <u>y</u> Cano	Deserveed	
	OK Apply Cano	Password:	
	<u>U</u> K Appl <u>y</u> Can	Pass <u>w</u> ord:	
<u>O</u> K Appl <u>y</u> Can		Pass <u>w</u> ord:	

CAD-MANUFACTURING SOLUTIONS, INC. PO Box 1261 Azle - Texas TX 76098 - USA Phone: +1 (501) 588-7970 (Sales support ONLY) Web: https://intellicadms.com Email: register@etoolbox.com

©1993-2021. CAD-MANUFACTURING SOLUTIONS, INC. IntelliCAD and the IntelliCAD logo are registered trademarks of the IntelliCAD Technology Consortium in the United States and other countries. All other trademarks are property of th respective owners.